



# Geotechnical instrumentation in practice

Purpose, performance and  
interpretation

Proceedings of the conference *Geotechnical instrumentation in civil engineering projects* organized by the Institution of Civil Engineers and co-sponsored by the British Geotechnical Society, the British Tunnelling Society and the British National Committee on Large Dams and held in Nottingham on 3-5 April 1989.

Conference organized by the Institution of Civil Engineers.  
Co-sponsored by the British Geotechnical Society, the British  
Tunnelling Society and the British National Committee on  
Large Dams.

Organizing Committee: P. A. F. Ferguson (Chairman),  
C. M. Cooling, P. Davies, M. F. Kennard, M. O'Reilly,  
B. O. Skipp, P. Tedd

British Library Cataloguing in Publication Data  
Geotechnical instrumentation in practice  
1. Engineering geology. Instrumentation  
I. Institution of Civil Engineers  
624.1'51'028

ISBN 0 7277-1515-1

First published 1990

© The Institution of Civil Engineers, 1989, 1990, unless otherwise stated.

All rights, including translations, reserved. Except for fair copying no part of this publication may be reproduced stored in a retrieval system, or transmitted in any form or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of the publisher. Requests should be directed to the Publications Manager, Thomas Telford Ltd, Telford House, 1 Heron Quay, London E14 9XF.

Papers or other contributions and the statements made or opinions expressed therein are published on the understanding that the author of the contribution is solely responsible for the opinions expressed in it and that its publication does not necessarily imply that such statements and/or opinions are or reflect the views or opinions of the ICE Council or ICE committees.

Published for the Institution of Civil Engineers by Thomas Telford Ltd, Telford House, 1 Heron Quay, London E14 9XF.

Printed and bound in Great Britain by  
Billings and Sons Ltd, Worcester.

## Contents

### Earthworks

1. Micros for embankment monitoring needn't cost the earth — the Creetown experience. D. C. MANN and D. C. HAMILTON 1
2. The application of instrumentation to the monitoring of ground treatment on an earthworks contract. V. C. S. AU and S. BUTTLING 25
3. A46 Lincoln Relief Road: geotechnical instrumentation on Lincoln Edge Escarpment J. H. BARLOW 41
5. Construction of a 21 metre high embankment based on instrumentation observations from simple monitoring devices. M. F. KENNARD and C. G. HOSKINS 59
- Rapporteur's paper. R. T. MURRAY 75
- Discussion 86

### Landslides and excavated slopes

8. Experience of a computerised monitoring system for landslides. B. MÖLLER, O. LINDHOLM and S. ARNEKULL 95
9. The behaviour of an instrumented dowel installed to stabilise slope movements. W. H. TING, C. T. TOH, P. K. CHOONG, T. F. WONG, and T. T. CHIAM 107
10. Instrumentation of temporary excavations for the A55 Conwy Crossing. J. N. DAVIES, P. WILLIAMS and K. G. WOODS 119
11. Global monitoring of unstable slopes in the North East of Portland, Dorset. J. N. McLAREN 145
12. Instrumentation systems for an experimental cut slope at Selborne, Hampshire — design and initial performance. M. R. COOPER, and D. I. GRANT 165
13. Continuous measurement of landslide movements. Ch. BONNARD and G. STEINMANN 117
- Rapporteur's paper. A. D. M. PENMAN 191
- Discussion 195

## P7. Behaviour of an instrumented reinforced embankment

M. FAVARETTI and A. MAZZUCATO, University of Padua

**SYNOPSIS.** The paper deals with the case of an overpass, composed of two reinforced earth embankments, linked by a three-span bridge. One of them has been instrumented with electric strain gauges. The Authors present a comparison between experimental and theoretical values of the tensile tension on three characteristic reinforcing elements.

### INSTRUMENTATION AND MEASUREMENTS.

1. The soil, used as granular fill, is a sandy gravel. A series of C.I.D. triaxial tests with increasing confining pressure were carried out. The triaxial specimens were compacted, with a rubber membrane around them, in a specially developed split mold (200 mm wide; 410 mm high). The failure curve on the Mohr plane was not linear. For the theoretical determination of the stresses in the reinforced embankment, an internal friction angle of  $50^\circ$  and an apparent cohesion of 0 were assumed.

2. Electric resistance strain gauges, for measuring the stresses developing on the reinforcing elements, were installed on a cross-section of the smaller embankment. Three characteristic reinforcing elements were chosen, respectively at +4.40 m, +2.90 m and +1.40 m from original ground level. The gauges were placed at various distances from the vertical facing, 3 on the upper strip, 4 on the middle one, and 3 on the deep one. The gauges were bonded in pairs to the top and bottom of the reinforcing elements to permit separation of axial and bending tension.

3. The distributions of axial tension on the instrumented reinforcing elements are presented in Fig.1. The values of the peak tension appear to be independent of depth. This behaviour conflicts with the conventional design approaches (tie-back analysis and coherent gravity analysis) in which it is assumed that, for constant spacing of the elements,

the tension will increase in direct proportion to the depth of the fill. This could be due to the stresses induced by compaction, having a dominating influence on those produced by the level of the fill, or to the rod, to which all the elements in a vertical profile are connected, that causes a redistribution of the tensile forces.

4. The line of maximum tension cannot be located. Anyway, apart from the deepest reinforcing element, the highest value of the axial stress was recorded at the point nearer the facing. The simple schemes, used for the calculation of the maximum axial stress and corresponding tensile force on each reinforcing element, gave values greater than experimentally recorded ones. This could be due to the extremely conservative values provided by the calculation scheme. Only on shallow element theoretical values match with experimental ones; proceeding downwards such differences tend to increase more and more.

5. Considering the shallow reinforcing element it has been determined the average mobilized coefficient of the interface friction soil-strip on the basis of the gradient between the peak tension and the rear of the element, where the tension must be equal to zero: we obtained a value of

0.29 much less than 1.2 proposed by Schlosser for ribbed strips.

6. Lastly, corrosion checking rod, 600 mm long, was positioned in the fill in 1984 and removed four years later. The weight loss was negligible and equal to 0.06% of its original weight.




Fig. 1